

Defender™ step type ladders

Ergonomic Defender step type ladders maximise comfort, ease of movement and safety.

Carrying **StandardsMark™** product certification, Defender access and safety equipment is designed by engineers, tested in a **NATA™-accredited** facility and installed by Certified Defender Installers.


Defender step type ladders fully comply with the **National Construction Code, AS 1657, OHS legislation and state regulations.**

Most importantly, every Defender step type ladder is individually built to suit your site and the way your people work. The result is strong, reliable equipment that delivers fully compliant access and true safety.

About the AS 1657 Standard

The AS 1657 Standard requires that the means of access shall be selected from the following limits of slope, and considered in the hierarchical order given:

Limits of slope



Defender's wide range of equipment includes all the means of access discussed in AS 1657, in addition to all components (stabilizing brackets, safety-lines, guardrails, hand-rails, cages, intermediate platforms/landings and platforms, lockable gates, access hatches, etc.), for a complete and safe height access system.

Quick delivery, minimal disruption

For rapid delivery, Defender step type ladders are stocked in our warehouse in kit form to suit all standard roof and platform profiles. Your Defender step type ladder can be installed with minimal disruption.

Other Specifications Guides in the **DEFENDER** series:

Access Hatches	Rung Ladders
Cooling Tower Platforms	Staircases
Guardrails	Static Lines & Rail Systems
Landings & Platforms	Walkways
Roof Anchors	Internal & Suspended Walkways



AS 1657 Approved

AS 1657 is the Australian Standard for the design, construction and installation of guardrails, fixed platforms, walkways, stairways and ladders. This standard underpins Defender's performance.

ISO 9001 Quality

ISO 9001 is the world's most established quality framework, currently being used by over 750,000 organisations in 161 countries. This standard assures Defender's quality.

NATA™ Accredited Testing

NATA is the authority that provides independent assurance of technical competence through a proven network of best practice industry experts. The criteria for determining a facility's competence are based on the relevant international standard (e.g. ISO/IEC 17025, ISO 15189, ISO/IEC 17020). NATA provides assessment, accreditation and training services to laboratories and technical facilities throughout Australia and internationally.

CodeMark™ – National Construction Code Approved

The CodeMark scheme recognises Defender's compliance with the National Construction Code (formerly the BCA).

Proudly Australian Made

Engineered and fabricated in its own ISO 9001 quality-assured factory, Defender guardrails are certified Australian-made.


Get it done right, first time, for less.
Defender equipment and installation is extraordinarily cost-effective. Why?
Because smart design shouldn't cost extra.

**CALL US TODAY ON 1300 013 794
TO ARRANGE A VISIT FROM A
CERTIFIED DEFENDER™ CONSULTANT**



Step Type Ladders

SPECIFICATIONS GUIDE



To order, receive a quote, or for more information contact us today at:

enquiries@workplacedefender.com.au

or call 1300 013 794

www.workplacedefender.com.au

Certified Defender™ Installer:

**workplace
access&safety®**

the fall prevention specialists

Telephone 1300 552 984

www.workplaceaccess.com.au



www.workplacedefender.com.au

Defender™ step type ladders

Ergonomic Defender step ladders maximise comfort, ease of movement and safety.

They are designed and independently certified to fully meet the requirements of Australia's **National Construction Code** (formerly the BCA) and **AS 1657**, ensuring compliance with **Australian Standards**, **OHS legislation** and **state regulations**.

Manufacture and installation specifications:

- > Ladder, with the correct accessories to meet AS 1657, to be installed at a 60-70 degree (1 in 4) incline wherever possible.
- > The stile to be made of an unbroken length of aluminium to avoid points of weakness. Splicing is unacceptable.
- > Brackets to be installed at correct intervals to maintain 250kg load rating.
- > Ensure a minimum 200mm clearance behind step ladders.
- > Treads, including the distance from the bottom tread to the landing, are to be equally spaced. (See figures 2 & 3.)
- > Dimensions and properties of step ladder to be fully compliant to AS 1657. (See Figures 4 & 5.)
- > Treads to be shaped to maximize foothold as proved in ergonomic research*. (See Figure 6.)
- > Positive fixings will be used: never rivets or Tek screws for primary structural fixings. All are to be galvanized and never zinc coated.
- > Provide slip resistance tests results confirming treads are independently tested in a *NATA™-accredited* laboratory to meet outdoor slip rating of R10 on a wet oil ramp test.
- > Rungs to be bolted, not welded, to the stiles, with additional mechanical fixings to provide redundancy, guaranteeing treads won't fail and dislodge from stiles.
- > Labelled to ensure traceability, identify parties and to nominate the load rating of the system.

*Caple, D, 2012 report

Testing

- > Tested in a *NATA™-accredited* laboratory to meet the seven mandatory AS 1657 tests for stile, rung, fixing, extended stile strength and durability.

Manufacture

- > Manufactured by an independently audited ISO 9001 accredited facility, delivering consistent product with full traceability.
- > Certified Australian-made

Documentation and labelling

- > Comprehensive handover documentation allows the system to be properly managed by the workplace controller.
- > Provides all of the user information, layouts and compliance labelling to meet AS 1657 safety requirements.

Installation

- > Height safety installers demonstrate competency through training delivered by a registered training organisation.
- > Independently-accredited installation contractor to install the step ladders.

Safe installation and fabrication

- > Installation performed by organization independently certified to AS/NZS 4801 Standard for Health and Safety Management Systems.
- > Licensed to the requirements of state building regulations.

Environmental accreditation

- > Manufacture and construction to be conducted by an organisation independently certified to satisfy the ISO 14001 Environmental Management System standard recognising the management of primary environmental issues.

Traceability

- > Mark all step ladders to provide full traceability to material batches.

Design

- > System layout and design to be completed by an RTO-trained designer.

Step Type Ladders

- > Provide certification by a body independently accredited by *SAI Global™* or equivalent to AS 1657.

Design Certification

- > Issue a design certificate guaranteeing the system meets the requirements of the Code of Practice (Safe Design of Structures 2012).

Labelling

- > Each step ladder individually marked with a unique ID number specifying the manufacturer, installer, certifier and next inspection due date on a label that is capable of withstanding at least 12 months of weather exposure. (See Figure 1.)

Figure 1.

DEFENDER™
LADDERS
www.workplacedefender.com.au

Job No. _____

STL- 0610 Registered design, patent pending

Inspection next due date: _____

Notes: _____

Installed by **workplace access&safety®**
1300 552 984

Certified by **CODEMARK™** **AUSTRALIAN MADE**



Health & Safety
AS/NZS 4801



Environment
ISO 14001



AS 1657
Approved
SMK40193

Figure 2.




Figure 3.





Figure 4.



Figure 5. Minimum dimensions and properties for components of access ladders - Step Type

COMPONENT	SHAPE	MATERIAL	SIZE (Minimum)	NOTE
Stile	Rectangular Hollow Section	Aluminum 6063-T6	100mm wide x 50mm deep x 2.5mm thick	
Tread	C-Section with slip resistant surface	Aluminum 6063-T6	102mm deep x 40mm wide x 2mm thick	Slip Resistant Surface (see Diagram*)

Figure 6.



Recommended designer, manufacturer, installer and certifier:

workplace access&safety®

Telephone 1300 552 984

www.workplaceaccess.com.au



© Copyright Workplace Access & Safety Pty Ltd. This material is subject to copyright and is provided to you, subject to the strict condition that it must not be reproduced or communicated to the public in whole or substantial part without the prior written permission of the copyright owner. If and when such permission is granted, the permits may only be reproduced in its entirety, without deletions, omissions, amendments or variations, unless expressly written permission otherwise has been granted by the copyright owner.

TITLE: DEFENDER™ – STEP TYPE LADDER

DWG. No. SM-005

SHEET 1 OF 1

SCALE: NONE

SIZE
A3